



Car-Grip Hose Clamp, screwable

special clamp for attaching Carflex Super and Master-PUR STEP hoses to mobile and stationary systems

Product Details

Construction / Material

- Specification of the connection solution: largely tension-resistant and largely leak-proof connection due to bridge profiles
- Clamp Design: clamp with housing, worm thread and clamping screw, clamping screw in sizes M5-M10 designed as slotted hexagon screw, clamp band with single or multiple bridges, spot welded bridge
- Material of the clamp: steel

Properties

- Chemical Properties: rust-protected
- Other: easy to assemble

Operating Temperature

Delivery Information

Application Areas

Customizing Options

Article Variants

| Article number | DN of the hose mm | Type | Clamping range mm |
|----------------|----------------------|--|----------------------|
| 001571 | 50 | for Carflex Super and Master-PUR Step in DN 50 | 45 - 65 |

| Article number | DN of the hose mm | Type | Clamping range mm |
|----------------|-------------------|---|-------------------|
| 001576 | 60/63 | for Carflex Super and Master-PUR Step in DN 60/63 | 55 - 75 |
| 001577 | 70/75 | for Carflex Super and Master-PUR Step in DN 70/75 | 65 - 85 |
| 001578 | DN: 75 | for Carflex Super and Master-PUR Step in DN 75 | 65 - 85 |
| 001580 | 80 | for Carflex Super and Master-PUR Step in DN 80 | 75 - 95 |
| 001582 | 100 | for Carflex Super and Master-PUR Step in DN 100 | 95 - 115 |
| 001585 | 120/125 | for Carflex Super and Master-PUR Step in DN 120/125 | 115 - 135 |
| 001586 | 140 | for Carflex Super and Master-PUR Step in DN 140 | 135 - 155 |
| 001587 | 150 | for Carflex Super and Master-PUR Step in DN 150 | 145 - 165 |
| 001588 | 160 | for Carflex Super and Master-PUR Step in DN 160 | 155 - 175 |
| 001590 | 180 | for Carflex Super and Master-PUR Step in DN 180 | 175 - 195 |
| 001591 | 200 | for Carflex Super and Master-PUR Step in DN 200 | 195 - 215 |
| 001592 | 250 | for Carflex Super and Master-PUR Step in DN 250 | 245 - 265 |

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

