



# Combiflex Clamp Connection Hinged Clamp

for clamp connections according to DIN 32676 series A

## Product Details

### Construction / Material

- Specification of the connection solution: liquid-tight connection
- Clamp Design: clamp with hinge, clamp with screw lock, clamping screw in sizes M5-M10 designed as slotted hexagon screw
- Material of the clamp: material complies with the food regulations of DIN 32676 Series A, stainless steel 1.4301

### Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals
- Mechanical Properties: excellent tensile and tear strength
- Other: can be sterilised with superheated steam

### Operating Temperature

### Delivery Information

### Application Areas

### Customizing Options

## Article Variants

Article number	DN of the hose mm	Piece weight kg	Connection mm mm
002463	40	0.23	40
002466	50	0.31	50

Article number	DN of the hose mm	Piece weight kg	Connection mm mm
002470	65	0.31	65
002474	80	0.41	80
002478	100	0.41	100
002481	125	1.17	125
005987	150	1.34	150

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
**+49 209 97077-112**

Product requests via  
[masterflex.de/en](https://masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

