

# Hose Clamp with Bolts, Steel quality W4, stainless steel 1.4301

Special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units

## **Product Details**

**Construction / Material** 

- Clamp Design: one-piece hose clamp with a clamping range 32/35mm to 201/213 mm, clamp band designet with a band width of approx. 20 - 25 mm, clamp band designed with a band thickness of approx. 1.0 - 1.8 mm, clamp with screw lock, clamping screw in sizes M5-M10 designed as slotted hexagon screw
- Material of the clamp: stainless steel 1.4301

#### **Properties**

- Chemical Properties: rust-protected
- **Operating Temperature**
- **Delivery Information**

**Application Areas** 

**Customizing Options** 

## **Article Variants**

Article number	Clamping range mm	width x thickness
002113	32 - 35	20 × 1,0
002116	40 - 43	20 × 1,0

Article number	Clamping range mm	width x thickness
002119	48 - 51	22 × 1,0
002123	56 - 59	22 × 1,0
002125	60 - 63	22 × 1,0
002129	68 - 73	25 × 1,5
002131	74 - 79	25 × 1,5
002134	80 - 85	25 x 1,5
002136	86 - 91	25 × 1,5
002139	98 - 103	25 × 1,5
002141	104 - 112	25 × 1,5
002145	113 - 121	25 x 1,5
002147	122 - 130	25 × 1,5
002150	140 - 148	25 x 1,5
002153	162 - 174	25 × 1,8
002156	175 - 187	25 × 1,8
002158	188 - 200	25 × 1,8
002160	201 - 213	25 × 1,8
002163	214 - 226	25 × 1,8
002167	250 - 268	25 × 1,0
002175	320 - 335	25 × 1,0
011100	92 - 97	25 × 1,5

Subject to technical changes and colour deviations

# **Delivery Variants**

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## **Disposal instructions**

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by phone: +49 209 97077-112

Product requests via masterflex.de/en

### Address Headquarters

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen

