Quick-Fix Clamp for Cone Flanges

for quick connections of Combiflex PU conical flanges, weld-on conical flanges and conical flanges with spigots, following DIN 3016

Product Details

Construction / Material

- Specification of the connection solution: quick-action clamp for conical flanges based on DIN 3016
- Clamp Design: clamp with turnbuckle, clamping screw in sizes M5-M10 designed as slotted hexagon screw, accidental opening is prevented by a safety pin
- Material of the clamp: stainless steel 1.4301, material grade W4

Properties

- Chemical Properties: stainless
- Other: easy to assemble

Article Variants

Article number	DN of the hose in mm	Piece weight in kg	Free space to open (R) in mm	Minimum free space (D) in mm
002183	50	0.2	103	147
002184	65	0.26	103	158
002185	80	0.29	103	169
002186	100	0.46	170	212
002187	125	0.78	186	241
002188	150	0.86	202	266
002189	160	0.91	207	275
002190	180	0.97	215	289
002191	200	1.05	228	313
002192	250	1.24	254	360

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by phone: **+46 300 1717 0**

Product requests via: **https://www.masterflex.se/**

Headquarters for your sales area

Masterflex Scandinavia AB

Kabelgatan 13
43437 Kungsbacka
Sweden