
## MASTERFLEX





# Master-PVC HF

Article Master No.: 000454

#### PVC Film/Foil Hose, medium-weight, flexible









microbe resistant

hydrolysis flexible resistant

medium moderatel heavy y pressure resistant

## **Product Details**

**Construction / Material** 

- Type of construction: film hose with embedded support coil
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: foil thickness between the spirals approx. 1.2 1.5 mm, depending on DN

#### **Properties**

- Chemical Properties: good resistance to oil, good resistance to chemicals, good resistance to alkaline solutions, good resistance to acids
- Flexibility: flexible
- Weight: medium heavy
- Pressure Resistance: moderately pressure resistant
- Colour: grey
- Other: high vacuum and good pressure resistance

#### **Operating Temperature**

- Temperature Range: -20 70
- short-term maximum temperature: peaks to 80 °C

#### **Delivery Information**

Delivery, type of production: order-related production

#### **Application Areas**

• Areas of application: Industry, Ventilation & Air-conditioning, Bulk & Construction, Chemistry, Food & Pharma, Conveying, lifting & feeding technology

#### **Customizing Options**

• optional item modification (on request): other lengths, other nominal widths, with customer-specific imprint

| Extended Article<br>Number | Article<br>number | Nominal Size<br>(DN)<br>mm | Outer<br>diameter<br>mm | Bending<br>radius*<br>mm | Weight<br>kg/m | Operating<br>pressure<br>bar | Negative<br>pressure<br>bar | Max. Production<br>length<br>m | Stock<br>Lengths<br>m | Length (standard lengths<br>available for order)<br>m |
|----------------------------|-------------------|----------------------------|-------------------------|--------------------------|----------------|------------------------------|-----------------------------|--------------------------------|-----------------------|---|
| 000454:38:x                | 000454            | 38                         | 45                      | 57                       | 0.46           | 2.15                         | 0.64                        | 15.00                          | /                     | 10  |
| 000454:51:x                | 000454            | 51                         | 59                      | 76                       | 0.62           | 1.87                         | 0.38                        | 15.00                          | /                     | 10  |
| 000454:70:x                | 000454            | 70                         | 78                      | 105                      | 0.85           | 1.30                         | 0.29                        | 15.00                          | /                     | 10  |
| 000454:76:x                | 000454            | 76                         | 84                      | 114                      | 0.92           | 1.24                         | 0.29                        | 15.00                          | /                     | 10  |
| 000454:90:x                | 000454            | 90                         | 98                      | 135                      | 1.09           | 1.10                         | 0.25                        | 15.00                          | /                     | 10  |
| 000454:102:x               | 000454            | 102                        | 111                     | 153                      | 1.26           | 0.98                         | 0.25                        | 15.00                          | /                     | 10  |
| 000454:152:x               | 000454            | 152                        | 163                     | 228                      | 1.97           | 0.48                         | 0.18                        | 15.00                          | /                     | 10  |
| 000454:203:x               | 000454            | 203                        | 214                     | 305                      | 2.73           | 0.29                         | 0.14                        | 15.00                          | /                     | 10  |
| 000454:250:x               | 000454            | 250                        | 262                     | 375                      | 3.67           | 0.20                         | 0.12                        | 15.00                          | /                     | 10  |
| 000454:300:x               | 000454            | 300                        | 312                     | 450                      | 4.41           | 0.15                         | 0.10                        | 15.00                          | /                     | 10  |
| 000454:400:x               | 000454            | 400                        | 412                     | 600                      | 5.87           | 0.10                         | 0.08                        | 15.00                          | /                     | 10  |

### **Article Variants**

All data refer to a medium and ambient temperature of +20°C. Specification of the bending radius related to the inside of the hose bend

Subject to technical changes and colour deviations

#### **Delivery Variants**

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

#### **Disposal instructions**

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

#### **Possible Connection Elements**



Master-Grip Hose Clamp, screwable Special clamp for fastening light and medium-weight, righthanded spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301 Special clamp for fastening light and medium-weight, righthanded spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Quick-Fix Clamp Special clamp for fastening light and medium-weight, righthand spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Heat Shrink Cuff Heat shrink sleeve for easy connection and sealing of hoses



Hose connector Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Hose Reducer, symmetrical Hose reducer for extending, connecting and joining light to medium weight hoses

#### Individual consultation

We offer consultation by phone: +49 209 97077-112

Product requests via masterflex.de/en

#### **Address Headquarters**

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen

